

# BRICK Thunder Dock TB3



## Product overview

### BRICK Thunder Dock TB3

The BRICK THUNDER DOCK is designed to connect a BRICK STORAGE CARTRIDGE or BRICK STORAGEplus via Thunderbolt™ 3 interface to a PC-System.

Easy to connect to any PC with integrated Thunderbolt™ 3 interface.

### Highlights

- High bandwidth data download
- Robust and reliable housing
- Works with BRICK STORAGE and BRICK STORAGEplus

## Technical Information

Supply voltage	12V DC 5A
Storage interface	BRICK STORAGE
PC interface	Thunderbolt™ 3
Housing dimensions	320 x 66 x 250 mm
Cooling	Active
Weight	approx. 3kg
Operating temperature	0°C to +40°C
Storage temperature	-40°C to +75°C
Air humidity	90% non-condensing
IP protection class	IP20

### Scope of delivery

Power cable IEC-320-C7 > CEE 7/16, 1.8m, black (Euro)  
 Power cable IEC-320-C7 > NEMA 1-15P, 1.8m, black (US, JP)  
 Thunderbolt 3 cable, 1m with ThunderLok 3L  
 Desktop type power supply 60W, 12V, 5A



### Name

BRICK THUNDER DOCK TB3

### Order-no.

B17575-BTD-004-0TB3

### Description

Thunderbolt™ 3 Docking Station for BRICK STORAGE

Alle Daten bei 25°C Umgebungstemperatur, falls nicht anders angegeben. / All data at nominal input and 25° C ambient temperature, if not marked otherwise. ▪ Alle Daten dienen nur Informationszwecken und sind nicht als zugesicherte Eigenschaften aufzufassen. / All data for information purposes only, no assured characteristics. ▪ Technische Änderungen ohne vorherige Ankündigung sowie Irrtümer vorbehalten. / Technical modifications without notice and errors reserved. ▪ Belastung mit Extremwerten über einen längeren Zeitraum kann die Zuverlässigkeit beeinflussen. / Strain with extreme values for a longer period may affect the reliability. ▪ Alle Trademarks und Logos sind Eigentum der jeweiligen Unternehmen. / All trademarks and logos are property of the concerning companies. In case of doubts the German version of the document is binding. © b-plus GmbH • Jun-21 • Version: 1.0